









# Hose Products Division








## Thermal Management Hoses

As equipment thermal management requirements evolve, Parker's Hose Products Division continues to meet those connection demands to cool the energy sources and components for an optimal level of performance. Our customers have grown accustomed to Parker leading the world in fluid power and conveyance. Thus, the thermal management product offering follows our tradition of excellence by offering a comprehensive solution strategy. Products with this symbol  are approved data center hoses.








### Product Recommendations By Market

	Hose Series	Hose Tube Mtl	Cooling Type	Elec Cooling	Off Hwy Equip	Mining	On Hwy Truck/Bus	Applicable Stds.
	801	NBR	Hyd Oil/Liq Cooling	●	●	●	●	MSHA, UL94 HB
	807	EPDM-P	Liquid Cooling	●	●		●	UL94 V-0
	836	PKR	Hyd Oil/Liq Cooling		●	●	●	MSHA
	627	EPDM-P	Liquid Cooling	●				UL94 HB
	629	EPDM-P	Liquid Cooling	●	●		●	UL94 V-0
	7181	EPDM	Liquid Cooling	●	●		●	SAE J20R3 D-2
	7390	EPDM-P	Liquid Cooling	●				UL94 V-0
	*7395	EPDM-P	Liquid Cooling	●	●		●	SAE J20R2 D-1
	*7219	NBR	Hyd Oil/Liq Cooling		●	●	●	
	**285	NEOPRENE	Refrigerant	●	●	●	●	SAE J3062 Type C Class 1
	**244	BUTYL	Refrigerant	●	●	●	●	SAE J2064 Type B Class 1

### Product Recommendations By Size (See individual page for actual ID)

	Hose Series	3.5	4	5	6	8	10	12	14	16	20	24	32	48
	801		●		●	●	●	●		●				
	807		●		●	●	●	●		●				
	836		●		●	●	●	●						
	627				●	●		●		●	●	●		
	629	●	●											
	7181		●	●	●	●	●	●		●				
	7390										●	●	●	●
	*7395					●	●	●	●	●	●	●	●	
	*7219					●	●	●		●	●	●	●	
	**285		●		●	●	●	●	●					
	**244									●	●	●		

### Product Recommendations By Pressure (Per Size)

	Hose Series	3.5	4	5	6	8	10	12	14	16	20	24	32	48
	801		350		350	300	300	300		200				
	807		150		150	150	150	150		100				
	836		400		400	400	350	350						
	627				150	150		150		150	150	150		
	629	150	150											
	7181		65	65	65	65	65	50		45				
	7390										150	150	150	150
	*7395					150	150	150	150	150	75	75	75	
	*7219					150	150	150		150	75	75	75	
	**285		500		500	500	500	500	500					
	**244									500	500	350		

\*Note: E-Z Form is designed to be used in extremely tight bends where traditional products will kink.

\*\*Note: Not recommended for non-refrigerant applications.

 **WARNING:** This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).

# Data Center Hose Application Chart

Application	Sizes (in 16th's)															
	3.5 (5.3mm)		4 (1/4")		6 (3/8")		8 (1/2")		12 (3/4")		16 (1")		20 (1-1/4")	24 (1-1/2")	32 (2")	48 (3")
Connection Type	Hose Barb & Clamp	Push-Lok	Hose Barb & Clamp	Push-Lok	Hose Barb & Clamp	Push-Lok	Hose Barb & Clamp	Push-Lok	Hose Barb & Clamp	Push-Lok	Hose Barb & Clamp	Push-Lok	Hose Barb & Clamp	Hose Barb & Clamp	Hose Barb & Clamp	Hose Barb & Clamp
Server Blade	629	N/A	629	807												
Jumper Hose					627, 7395	807	627, 7395	807								
CDU Hose									627, 7395	807	627, 7395	807	627/7390	627/7390	7390	7390




## Push-Lok Hose System

Since 1968 customers have relied on Parker's Push-Lok Hose System for a reliable, durable, leak free hose assembly. The design of the Push-Lok hose and fitting are a highly engineered system that has been rigorously tested for leakage, coupling retention, and burst. The Push-Lok system is easy to use requiring no clamps or special tools during installation. The Parker Push-Lok assembly can be made in seconds, saving valuable time and cost. Push-Lok 82 series fittings are reusable, which can be replaced at the job site without any special tools or clamps. Its unique seal ensures reliable, durable, leak-free service. Outstanding quality, valuable efficiency and Parker's leak-free assurance are what you get with Parker Push-Lok hose and fitting system. The industry's most complete line of low-pressure hose and fittings, Push-Lok has been offering the range and versatility to meet all your needs for over 50 yrs. Now that is reliability!

### Reasons to use Push-Lok:

- Leak Free Technology
- Eliminates Clamps
- Eliminates Improper Clamp Positioning
- Faster Assembly Time
- Field Attachable and Reusable
- Manufacturer Qualified Assembly
- Reliable
- Proven History
- Color Coding Capability



## 801 – Push-Lok Plus®

Multipurpose

Available Cover Colors:



[view on web page](#)

# Part Number	Hose I.D.		Hose O.D.		Working Pressure		Minimum Bend Radius		Weight		Vacuum Rating		Parkrimp HY Series	Field Attachable 82 Series
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs/ft	kg/m	inches of Hg	kPa		
801-4	1/4	6,3	0.50	12,7	350	2,4	2-1/2	65	0.09	0,13	28	95	•	•
801-6	3/8	10	0.63	15,9	350	2,4	3	75	0.11	0,16	28	95	•	•
801-8	1/2	12,5	0.78	19,8	300	2,1	5	125	0.18	0,27	28	95	•	•
801-10	5/8	16	0.91	23,0	300	2,1	6	150	0.19	0,28	15	51	•	•
801-12	3/4	19	1.03	26,2	300	2,1	7	180	0.24	0,36	15	51	•	•
801-16	1	25	1.28	32,6	200	1,4	10	250	0.37	0,55	15	51	•	•

**Application:** Pneumatic, petroleum base hydraulic fluid, lubricating oils, and antifreeze solutions (not suitable for dry air applications).

**Diesel fuel:** approved only when coupled with HY Series fittings.

**Inner Tube:** Synthetic rubber.

**Reinforcement:** One fiber braid.

**Cover:** Synthetic rubber, MSHA accepted, UL94 HB rated

**Temp Range:** Air: +158° F (+70° C); Water: +185° F (+85° C);

Oil: -40° F to 257° F (-40° C to +125° C).

• Push-Lok is not recommended for any refrigerant, or for use in air conditioners and heat pump applications.

• Push-Lok is not recommended for applications where extreme pulsation is encountered.

• 801 hose is not approved with any HY Series stainless steel fittings.

**WARNING:** This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).

## 807 – Push-Lok EPDM-P

Air/Water/Coolant

Available Cover Colors:



[view on web page](#)

# Part Number	Hose I.D.		Hose O.D.		Working Pressure		Minimum Bend Radius		Weight		Vacuum Rating		Field Attachable 82 Series
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs/ft	kg/m	inches of Hg	kPa	
807-4-BLK-RL	1/4	6,4	0.48	12,1	150	1,0	1.0	25.4	0.08	0,12	15	51	•
807-6-BLK-RL	3/8	9,5	0.63	15,9	150	1,0	1.5	38.1	0.11	0,17	15	51	•
807-8-BLK-RL	1/2	12,7	0.81	20,6	150	1,0	2.8	69.9	0.17	0,25	15	51	•
807-10-BLK-RL	5/8	15,9	0.91	23,1	150	1,0	3.5	88.9	0.20	0,30	15	51	•
807-12-BLK-RL	3/4	19,1	1.05	26,7	150	1,0	4.5	114.3	0.25	0,37	15	51	•
807-16-BLK-RL	1	25,4	1.28	32,6	100	0,7	6.5	152.4	0.31	0,46	10	34	•

**Tube:** Black EPDM, peroxide cured

**Reinforcement:** One fiber braid

**Cover:** Black, red, and blue, synthetic rubber; smooth finish

**Temperature Range:** -40°F to +212°F (-40°C to +100°C)

**Brand Method:** White ink

**Brand Example:** Parker 807-16 PUSH-LOK EPDM-P;

WP 1MPa (100 psi) 25,4mm (1"); UL94 V-0 HOSE COVER MADE IN USA

**Design Factor:** 4:1

**Industry Standards:** UL94 V-0 flame resistance rating

**Application:** DI water and glycol based coolant solutions, air and phosphate ester

**Vacuum:** 15 in hg (sizes -4 through -12); 10 in hg (size -16)

**Couplings:** Designed to be used with 82 series fittings

**WARNING:** This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).

## 836 – Push-Lok Plus®

Multipurpose

Available Cover Colors:



[view on web page](#)

# Part Number	Hose I.D.		Hose O.D.		Working Pressure		Minimum Bend Radius		Weight		Vacuum Rating		Parkrimp HY Series	Field Attachable 82 Series
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs/ft	kg/m	inches of Hg	kPa		
836-4	1/4	6,3	0.50	12,7	400	2,8	2-1/2	65	0.09	0,13	28	95	•	•
836-6	3/8	10	0.63	15,9	400	2,8	3	75	0.11	0,16	28	95	•	•
836-8	1/2	12,5	0.78	19,8	400	2,8	4	100	0.18	0,27	28	95	•	•
836-10	5/8	16	0.91	23,0	350	2,4	5	125	0.19	0,28	18	61	•	•
836-12	3/4	19	1.03	26,2	300	2,1	6	150	0.24	0,36	18	61	•	•

**Application:** Pneumatic, petroleum base hydraulic fluid, lubricating oils, diesel fuels and antifreeze solutions.

**Inner Tube:** PKR®.

**Reinforcement:** One fiber braid.

**Cover:** PKR, MSHA accepted.

**Temp Range:** Air: +212° F (+100° C).

Water: +185° F (+85° C).

Oil: -55° F to +302° F (-48° C to +150° C).

Diesel fuels: -40° F to 302° F (-40° C to 150° C) with HY crimps only.

**Fittings:** HY Series, 82 Series

**WARNING:** This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).

# Push-Lok Assembly and Disassembly Steps

## Assembly is easy

1. Cut hose cleanly and squarely with a sharp knife or a Parker Push-Lok cut-off tool.
2. Lubricate the Push-Lok fitting and/or Hose I.D. with a light oil or soapy water only. Do not use heavy oil or grease.
3. Insert fitting into hose until the barb is in the hose.
4. Place end fitting against a flat object (bench or wall). Grip hose approximately one inch from end and push with steady force until the end of the hose bottoms on the fitting and is covered by the yellow plastic cap.



## Disassembles fast

1. Leave fitting in place and cut hose lengthwise from the yellow cap approximately one inch.  
**IMPORTANT:** Be careful not to nick barbs when cutting hose.
2. Grip hose and give a sharp downward tug to disengage the fitting.



Caution: Push-Lok fittings will properly grip Push-Lok hose only when pushed all the way in with the cut end of the hose completely concealed by the yellow plastic cap.

Sealing integrity may be damaged by using exterior clamps.



## Push-Lok Hose Cutters

Use Parker Push-Lok hose cutters to ensure quick and easy cutting. They are designed for use on all Push-Lok hose sizes and non-wire hose up to 1-1/8" O.D.

### TH11 - 1 Hose Cutter

Designed to squarely cut Push-Lok hose 1/4" I.D. through 3/4" I.D.



### 881540

#### Hose Cutter with Toggle

This unique tool combines a hose cutter with a toggle action that presses the fitting into the hose, making every job easier, whether you are making one assembly or a hundred. It is designed to handle Push-Lok hose from 1/4" through 3/4".

**Overall length:** 16"

**Weight:** approximately 4 pounds





# The Most Flexible Route from Hose Application to Hose Installation

E-Z Form™ hose provides extreme flexibility for easy and quick installation of coolant, water and oil suction/return lines on mobile and industrial equipment.

Available in multiple incremental sizes, E-Z Form hose:

- minimizes the need for costly made-to-order pre-formed hose and metal tubing,
- lowers the number of connections and potential leak points,
- reduces installation time,
- provides rapid delivery from stock and
- does not require dedicated inventory.

Designed to handle extreme bends while allowing full-flow, kink-free performance, E-Z Form hose effectively replaces preformed hoses and hose/bent metal tube assemblies in many applications – eliminating special design, tooling and fabrication costs and associated long lead times. E-Z Form hose is available in three distinct versions, all of which

incorporate a helical wire for full suction/vacuum service.

Parker has qualified E-Z Form hose with multiple styles of crimp fittings in popular sizes and configurations. For fitting and crimp specifications, refer to Crimpsource® at [www.parker.com/crimpsource](http://www.parker.com/crimpsource).

Crimpsource provides easy access to all the specifications necessary to correctly fabricate a factory quality hose assembly. You can also print a simple-to-follow data specification sheet or crimper decal.

## Off-the-Shelf Convenience and Dramatic Cost Reduction Opportunities

E-Z Form hose is designed and manufactured as a versatile, solution-driven product for OEM and aftermarket-related applications.

### Hose Problem

- ☐ Excessive time/labor to design, develop and procure prototypes
- ☐ High cost of made-to-order tooling
- ☐ High cost of low-volume formed hoses and bent metal tubes
- ☐ Multiple leak points inherent in hose/tube combination assemblies
- ☐ Significant time/labor required to install hose/tubes in tight routing applications
- ☐ Other hoses consume more footage due to “rounding out” the required bends
- ☐ Cost of inventory/management/storage of numerous formed hose SKUs
- ☐ Cost of inventory/management/storage of shaped adapters and special fittings

### E-Z Form Hose Solution

- ☒ E-Z Form is a catalog product available from stock in multiple incremental sizes
- ☒ One continuous length of hose minimizes leak points and subsequent warranty issues
- ☒ Extreme flexibility streamlines installation and eliminates the need to braze metal tubes
- ☒ Extreme flexibility allows a more direct path in routing
- ☒ Replaces many made-to-order hoses; Packaged in convenient reels and coils and can be cut to length as needed
- ☒ Extreme flexibility permits efficient hose routing while minimizing the need for adapters and/or special fittings

## 7395 – E-Z FORM™ GS General Service Hose



[view on web page](#)

Series 7395 hose incorporates a tube that is resistant to commonly used coolant mixtures, a wire helix for full suction/vacuum capability and a path to conduct a static electrical charge to ground, and a cover that is resistant to abrasion, mild chemicals, heat and ozone. The unique Greek cover corrugations are precision-engineered, providing extreme flexibility for routing through confined spaces eliminating the need for formed hose.

**NOTE: Do not drag across sharp edges or highly abrasive surfaces.**

# Part Number	Hose I.D.		Reinf Layers	Hose O.D.		Approx Wt		Minimum Bend Radius		Max WP		Perm Cplg Rec	Nom Std Pack Qty (ft)	Pkg Type
	inch	mm		inch	mm	lbs/ft	kg/m	inch	mm	psi	MPa			
7395-0375300	3/8	9,5	2	0.8	20,8	0.24	0,36	0.9	24,1	150	1,03	*	300	Reel
7395-0500025	1/2	12,7	2	0.9	23,8	0.27	0,40	0.9	24,1	150	1,03	HY	25	Carton
7395-0500300													300	Reel
7395-0625025	5/8	15,9	2	1.1	27,0	0.33	0,49	1.3	32,7	150	1,03	HY	25	Carton
7395-0625300													300	Reel
7395-0750025	3/4	19,1	2	1.2	30,0	0.35	0,52	1.4	36,3	150	1,03	HY/43	25	Carton
7395-0750300													300	Reel
7395-0875025	7/8	22,2	2	1.3	32,8	0.38	0,57	1.4	36,3	150	1,03	*	25	Carton
7395-0875300													300	Reel
7395-1000025	1	25,4	2	1.4	36,0	0.41	0,61	1.4	36,3	150	1,03	HY/43	25	Carton
7395-1000300													300	Reel
7395-1000300-RED	1	25,4	2	1.4	36,0	0.41	0,61	1.4	36,3	150	1,03	HY/43	300	Reel

**Tube:** Peroxide cured EPDM for sizes up through 1";  
Sulfur cured for sizes above 1"

**Reinforcement:** Multiple textile braids or plies with wire helix

**Cover:** Black EPDM; Greek corrugated finish

**Temp. Range:** -50° F to +257° F (-45° C to +125° C)

**Brand Method:** Black text on blue stripe

**Brand Example:** PARKER SERIES 7395 E-Z FORM™ GS  
HOSE XXX PSI MAX WP

**Design Factor:** 4:1

**Industry Standards:** SAE J20R2-D1 performance  
UL94 flame resistance rating HB; through 1"

**Applications:**

- Air, coolant, mild chemicals, water
  - Coolant systems, drain lines, vacuum service
  - SAE-performance in engine coolant service, general industrial
- Vacuum:** 29" Hg (737 mm Hg)

**WARNING:** This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).

## 7390 – E-Z FORM™ GS General Service Hose



[view on web page](#)

# Part Number	Hose I.D.		Reinf Layers	Hose O.D.		Approx Wt		Minimum Bend Radius		Max WP		Perm Cplg Rec	Nom Std Pack Qty (ft)	Pkg Type
	inch	mm		inch	mm	lbs/ft	kg/m	inch	mm	psi	MPa			
7390-1250100	1 1/4	31,8	2	1.70	44,3	0.50	0,75	2.2	55,9	150	1,03	N/A	100	Coils
7390-1500100	1 1/2	38,1	2	1.90	50,5	0.58	0,86	2.9	73,7	150	1,03	N/A	100	Coils
7390-2000100	2	50,8	2	2.50	65,0	0.96	1,43	4.6	116,8	150	1,03	N/A	100	Coils
7390-3000100	3	76,2	2	3.50	90,5	1.51	2,25	8.8	223,5	150	1,03	N/A	100	Coils

**Tube:** Black EPDM, peroxide cured

**Reinforcement:** Multiple textile braids or plies with wire helix

**Cover:** Black synthetic rubber; greek corrugated

**Temperature Range:** -40°F to +212°F (-40°C to +100°C)

**Brand:** Mylar Blue (-BLYL) or Red (-RLYL) for color coding

**Brand Example:** Parker Series 7390 E-Z Form EPDM-P Hose

**Design Factor:** 4:1

**Industry Standards:** UL94 V-0 flame resistance rating

**Application:** DI water and glycol based coolant solutions

**Vacuum:** Full

**WARNING:** This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).

# 7219 – E-Z FORM™ MP

## Multipurpose Oil Resistant Hose



[view on web page](#)

Series 7219 hose construction incorporates a tube that is resistant to a oil and refined fuels, a wire helix that provides full suction/vacuum capability and a path to conduct a static electrical charge to ground, and a cover that is resistant to oil and weathering. The unique Greek corrugations are tightly pitched and precision-engineered, providing minimal force-to-bend, superior kink resistance, extreme flexibility and allow for routing through confined spaces where formed hose is normally required.

- NOTES:**
- Do not use in fuel dispensing or service applications requiring API, NFPA, UL, ULC or any other agency approval or listing.
  - Refer to the Refined Fuel/Hose Compatibility Table in the Media Compatibility section.
  - Do not drag across sharp edges or highly abrasive surfaces.

# Part Number	Hose I.D.		Reinf Layers	Hose O.D.		Approx Wt		Minimum Bend Radius		Max WP		Perm Cplg Rec	Nom Std Pack Qty ft	Pkg Type
	inch	mm		inch	mm	lbs/ft	kg/m	inch	mm	psi	MPa			
7219-0500025	1/2	12,7	2	0.9	23,8	0.27	0,40	0.9	24,1	150	1,03	HY	25	Carton
7219-0500300													300	Reel
7219-0625025	5/8	15,9	2	1.1	27,0	0.33	0,49	1.3	32,7	150	1,03	HY	25	Carton
7219-0625300													300	Reel
7219-0750025	3/4	19,1	2	1.2	30,0	0.35	0,52	1.4	36,3	150	1,03	HY/43	25	Carton
7219-0750300													300	Reel
7219-1000025	1	25,4	2	1.4	36,0	0.41	0,61	1.4	36,3	150	1,03	HY/43	25	Carton
7219-1000300													300	Reel
7219-1250025	1-1/4	31,8	2	1.7	43,0	0.50	0,75	2.2	56,7	75	0,52	HY/43	25	Carton
7219-1250130													130	Coil
7219-1500025	1-1/2	38,1	2	1.9	49,0	0.58	0,86	2.9	74,1	75	0,52	43	25	Carton
7219-1500130													130	Coil
7219-1625025	1-5/8	41,3	2	2.1	53,0	0.64	0,95	3.6	92,4	75	0,52	*	25	Carton
7219-1750025	1-3/4	44,5	2	2.2	56,0	0.68	1,01	4.0	101,0	75	0,52	*	25	Carton
7219-2000025	2	50,8	2	2.5	63,0	0.96	1,43	4.6	117,4	75	0,52	43	25	Carton
7219-2000130													130	Coil

**Tube:** Black nitrile

**Reinforcement:** Multiple textile plies with wire helix

**Cover:** Black chloroprene; Greek corrugated finish

**Temp. Range:** Sizes 1/2", 5/8", 3/4" and 1": -30° F to +250° F  
(-34° C to +121° C)  
All other sizes: -30° F to +212° F  
(-34° C to +100° C)

**Brand Method:** Black text on red stripe

**Brand Example:** PARKER SERIES 7219 E-Z FORM™ MP  
HOSE 75 PSI MAXWP

**Design Factor:** 4:1

**Industry Standards:** None applicable

**Applications:**

- Biodiesel (to B20 in dedicated and non-dedicated service), diesel, ethanol, gasoline, oil
- Oil suction/return lines; vehicle fuel fill connector lines; drain lines
- Buses, cranes, mobile off-road equipment

**Vacuum:** 29" Hg (737 mm Hg)

**WARNING:** This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).

# Thermal Cooling Products

627 

## Thermal Cooling Hose

Parker's 627 is designed to be utilized for the transfer of coolants in high performance computers and data farms. The tube is specially formulated and compounded peroxide cured EPDM for compatibility with industrial coolants.



[view on web page](#)

# Part Number	Hose I.D. inch mm		Reinf Layers	Hose O.D. inch mm		Approx Wt lbs/ft kg/m		Minimum Bend Radius inch mm		Max WP psi MPa		Perm Cplg Rec	Pkg Type
627-6-RL	3/8	9,5	2	0.7	16,7	0.13	0,19	1.3	33,0	150	1,03	HY	Reel
627-8-RL	1/2	12,7	4	0.9	22,7	0.24	0,36	2.0	50,8	150	1,03	HY	Reel
627-12-RL	3/4	19,1	4	1.2	29,4	0.34	0,51	3.0	76,2	150	1,03	HY	Reel
627-16-RL	1	25,4	4	1.4	36,3	0.46	0,68	4.5	114,3	150	1,03	HY	Reel
627-20-RL	1 1/4	31,8	4	1.8	45,7	0.67	1,01	6.5	165,1	150	1,03	HY	Reel
627-24-RL	1 1/2	38,1	4	2	50,8	0.84	1,24	9	228,6	150	1,03	43	Reel

**Tube:** Black EPDM, peroxide cured

**Reinforcement:** Multiple textile plies

**Cover:** Black Synthetic Rubber; smooth finish

**Temperature Range:** -40°F to +212°F (-40°C to +100°C)

**Brand Method:** White ink

**Brand Example:** Parker Series 627

**Design Factor:** 4:1

**Industry Standards:** UL94 HB flame resistance rating

**Application:** DI water and glycol-based coolant solutions

**Couplings:** Designed to be used on hose barb and clamped

**WARNING:** This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).









629 

## Server Blade Hose

Parker's 629 is designed to be utilized for the transfer of coolants in high performance computers and data farms. The tube is specially formulated and compounded peroxide cured EPDM for compatibility with industrial coolants.



[view on web page](#)

#														Std Pack Qty ft	
Part Number	ID (in)	ID (mm)	OD (in)	OD (mm)	B.R. (in)	B.R. (mm)	WP (psi)	WP (MPa)	Weight (lbs/ft) (kg/m)		Vacuum Rating (in HG) (kPa)		Series Cplg Rec		Pkg Type
629-3.5-RL	0.21	5,3	0.38	9,7	0.6	16,0	150	1,03	0.05	0,07	28	95	N/A	500	Reel
629-4-RL	0.25	6,4	0.44	11,2	0.8	19,1	150	1,03	0.08	0,12	28	95	N/A	600	Reel

**Tube:** Black EPDM, peroxide cured

**Reinforcement:** One fiber braid

**Cover:** Black Synthetic Rubber; smooth finish

**Temperature Range:** -40°F to +212°F (-40°C to +100°C)

**Brand Method:** White ink

**Brand Example:** Parker 629-4 HOSE EPDM-P WP 1MPa (150 psi) 6,4mm (1/4") UL94 V-0 HOSE COVER MADE IN USA

**Design Factor:** 4:1

**Industry Standards:** UL94 V-0 flame resistance rating

**Application:** DI water and glycol-based coolant solutions

**Couplings:** Designed to be used on hose barb and clamped

**WARNING:** This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).



# 7181 Heater Hose

Parker's 7181 hose construction designed to SAEJ20R3 D-2 provides electrochemical resistance (ECR) to inhibit striations and rusting of hose-to-metal interfaces, and high temperature performance. The hose is resistant to abrasion, mild chemicals and weathering.



[view on web page](#)

# Part Number	Hose I.D.		Reinf Layers	Hose O.D.		Approx Wt		Minimum Bend Radius		Max WP		Perm Cplg Rec	Nom Std Pack Qty ft	Pkg Type
	inch	mm		inch	mm	lbs/ft	kg/m	inch	mm	psi	MPa			
7181-251	1/4	6,4	2	0.5	13,4	0.10	0,15	3	76,2	65	0,45	*	700	Reel
7181-311	5/16	8,0	2	0.6	15,0	0.18	0,27	5	127,0	65	0,45	*	700	Reel
7181-381	3/8	9,5	2	0.7	17,5	0.16	0,24	5	127,0	65	0,45	*	600	Reel
7181-501	1/2	12,7	2	0.8	20,7	0.19	0,28	6	152,4	65	0,45	*	500	Reel
7181-631	5/8	15,9	2	0.9	23,9	0.23	0,34	8	203,2	65	0,45	HY	500	Reel
7181-631050	5/8	15,9	2	0.9	23,9	0.23	0,37	8	203,2	65	0,45	HY	5 x 50	Carton
7181-751	3/4	19,1	2	1.1	27,1	0.27	0,40	9	228,6	50	0,34	*	500	Reel
7181-1001	1	25,4	2	1.3	34,0	0.37	0,55	12	304,8	45	0,31	*	300	Reel

**Tube:** Black EPDM

**Reinforcement:** Multiple textile plies

**Cover:** Black EPDM; smooth finish

**Temp. Range:** -40° F to +257° F (-40° C to +125° C)

**Brand Method:** White ink

**Brand Example:** PARKER SERIES 7181 HEATER HOSE  
SAE 20R3EC D-2 (ID) XX PSI MAX WP  
ELECTROCHEMICALLY RESISTANT

**WARNING:** This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).

# Refrigerant Hose Products

## 285 Refrigerant SAE J3062 TYPE C



[view on web page](#)

# Part Number	Hose I.D.		Hose O.D.		Working Pressure		Minimum Bend Radius		Weight		Vacuum Rating		Parkrimp 26 Series
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs/ft	kg/m	inches of Hg	kPa	
285-4	3/16	5,1	0.5	12,5	500	3,45	1	25	0.09	0,13	28	95	•
285-6	5/16	8,2	0.6	14,7	500	3,45	1-1/2	40	0.10	0,14	28	95	•
285-8	13/32	10,7	0.7	17,3	500	3,45	2	50	0.13	0,17	28	95	•
285-10	1/2	12,9	0.8	19,4	500	3,45	2-1/2	65	0.15	0,19	28	95	•
285-12	5/8	16,1	0.9	23,6	500	3,45	3	75	0.19	0,27	28	95	•
285-14	3/4	19,1	1.1	27,4	500	3,45	3-1/2	89	0.24	0,34	28	95	

**Application:** Refrigerants R134a / PAG Oil & R1234yf / PAG Oil.

**Inner Tube:** Synthetic rubber with nylon barrier.

**Reinforcement:** One fiber braid.

**Cover:** Synthetic rubber.

**Temperature Range:** -40° F to +257° F (-40° C to +125° C).

**Fittings:** 26 Series

**WARNING:** This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).

# 244 Refrigerant

SAE J2064 B CLASS I



[view on web page](#)

# Part Number	Hose I.D.		Hose O.D.		Working Pressure		Minimum Bend Radius		Weight		Vacuum Rating		Parkrimp 26 Series
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs/ft	kg/m	inches of Hg	kPa	
244-16	7/8	22	1.23	31	500	3,45	7-1/2	190	0.51	0,76	28	95	•
244-20	1-1/8	29	1.50	38	500	3,45	9	230	0.56	0,83	28	95	•
244-24	1-3/8	35	1.75	44	350	2,41	10-1/2	270	0.62	0,92	28	95	•

**Application:** Refrigerant 134a.

**Inner Tube:** Butyl rubber.

**Reinforcement:** One-braid steel wire.

**Cover:** Fiber braid.

**Temperature Range:** -22° F to +257° F (-30° C to +125° C).

**Fittings:** 26 Series.

**WARNING:** This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).

To find catalog information on the multiple fitting series scan the QR Codes which will take you directly to the page.



26 Series



43 Series



82 Series



HY Series

